



Designed,
Developed &
Manufactured In India



GX206

FSK SUPPORTABLE PBX



System Features

- Caller-ID Detection[FSK & DTMF]
- Over Voltage Protection
- Inbuilt Lightning Arrester
- Attractive Metal Cabinet
- Flexible Mounting Option: Wall Mount / Desktop
- Power Failure Transfer
- Surge Current Protection
- 100% Full Load Burn-in Test
- Trunk & Extension LED Monitor
- Extension Line Voltage: 28Vdc
- Ringer Voltage: 75Vac

Extension Features

- Making an Intercom Call
- Making an Outside Call
- Holding a Call
- Camped Call
- Auto Call Back
- Call Camp On
- Call Follow Me
- Call Forward Anytime
- Call Forward During Busy
- Call Transfer While Ringing
- Call Transfer with Consult
- Trunk Waiting Call Pickup
- Emergency Reporting
- Flexible Numbering
- Remote Programming
- Trunk Redial
- Direct Inward Dialing
- Paging
- Hot Line
- Conference
- Do Not Disturb
- Call Pickup
- Call Privacy
- Call Split
- Broker Call
- Barge-in
- Feature Cancellation
- Global Memory Dialing (100 Nos)
- Least Cost Routing
- Room to Room Calling

Technical Specification

Trunk (Max.)	2
Extension (Max.)	6
AC Voltage	230V / 50Hz
Power Consumption	17W (Max.)
Dimension	265*190*55mm
Environment	0 ° to +45 °C, 20% to 80% Humidity




Caller-ID



Conference



Call Back



Auto Attendant



Paging